

The package **EASYMAT**

Enrico Bertolazzi

Department of Mechanics and Structures Engineering
University of Trento
via Mesiano 77, I – 38050 Trento, Italy

enrico.bertolazzi@ing.unitn.it

19th March 2002

Abstract

The **EASYMAT** package is a macro package for supporting block matrices having equal column widths or equal rows heights or both, and supporting various kinds of rules (lines) between rows and columns. The package is based on an array/tabular-like syntax.

Contents

| | | |
|---|--|----|
| 1 | Some examples with EASYMAT | 2 |
| 2 | Some example with balancing | 5 |
| 3 | An example with minimal size setting | 6 |
| 4 | An example with various size rules | 7 |
| 5 | The \addpath command | 8 |
| 6 | An example with reentrance | 10 |

1 Some examples with EASYMAT

The package is loaded by means the usual way:

```
\documentclass{article}
.
.
\usepackage[thinlines,thicklines]{easymat}
.
.
```

The options `thinlines` and `thicklines` are self explanatory. EASYMAT provides the `MAT` environment which is a simple re-implementation of the array/tabular environment, with some limitation and some additional features. The syntax is

```
\begin{MAT}{(eq)}{[ex]}{(cc...c)}
  a & b & ... & n \\
  ...
\end{MAT}
```

or

```
\begin{MAT}{(eq, mx, my)}{[ex, MX, MY]}{(cc...c)}
  a & b & ... & n \\
  ...
\end{MAT}
```

- (`eq`) or (`eq, mx, my`). By `eq` you can balance the rows or the column or both, as shown in this table:

Table 1.

| value of <code>eq</code> | effect |
|--------------------------|--|
| <code>@</code> | no balancing |
| <code>r</code> | equal rows heights |
| <code>c</code> | equal column widths |
| <code>b</code> | equal rows heights and equal column widths |
| <code>e</code> | equal rows heights and column widths |

By `mx` and `my` you can modify the minimum size of the box in the MAT environment. This must be a valid measure e.g. `2pt`. This is useful in writing matrices and vectors.

- **[ex]** or **[ex, MX, MY]**. By **ex** you can specify the amount of extra space around the item in the **MAT** environment. The default is **2pt**. By **MX** and **MY** you can modify the minimum size of the whole table in the **TAB** environment. This must be a valid measure e.g. **10cm**.
- The '**{cc...c}**' is the definition of the columns and their alignment. The possible alignment for the columns are:

Table 2.

| | |
|----------|-------------|
| c | centering |
| l | flush left |
| r | flush right |

IMPORTANT: The package can manage matrices with a maximum of **30** rows by **30** columns.

It is possible to produce rules among columns or rows as this example shows:

```
\[ \begin{MAT} (b) {|l:cr|}
  \first-
  \aligntop
  1 & 1 & 1 \\
  1 & \frac{111}{222} & 1 \\
  \alignbottom
  1 & 1 & 1 \\
\end{MAT}
\qquad
\begin{MAT} (b) {|r:c1|}
  \first-
  \alignbottom
  1 & 1 & 1 \\
  1 & \frac{111}{222} & 1 \\
  \aligntop
  1 & 1 & 1 \\
\end{MAT}
\]
```

The figure shows two matrices labeled (b) and (b'). Matrix (b) consists of three columns and three rows. The first column contains '1' in all positions. The second column contains '1' in the first and third rows, and a fraction $\frac{111}{222}$ in the middle row. The third column contains '1' in the first and third rows, and '1' in the middle row. Matrix (b') also has three columns and three rows. The first column contains '1' in all positions. The second column contains '1' in the first and third rows, and a fraction $\frac{111}{222}$ in the middle row. The third column contains '1' in the first and third rows, and '1' in the middle row. The two matrices are separated by a horizontal line.

The command `\first` is used to produce the first top rule. The various separation rules are defined by a character code immediately after the command `\\"`. The available rules for the rows and columns are


Table 3.

| | |
|----------------|--|
| nothing | no rule |
| <code> </code> | solid line (or <code>-</code> for the rows) |
| <code>:</code> | dash line |
| <code>;</code> | dot-dash line |
| <code>.</code> | dotted line |
| <code>0</code> | solid line with size 1/5 of normal line |
| <code>1</code> | solid line with size 1/4 of normal line |
| <code>2</code> | solid line with size 1/3 of normal line |
| <code>3</code> | solid line with size 1/2 of normal line |
| <code>4</code> | equivalent to <code> </code> |
| <code>5</code> | solid line with size 2 times of normal line |
| <code>6</code> | solid line with size 3 times of normal line |
| <code>7</code> | solid line with size 4 times of normal line |
| <code>8</code> | solid line with size 5 times of normal line |
| <code>9</code> | solid line with size 6 times of normal line |

IMPORTANT: each row **must** end with `\\"` otherwise an error is produced.

The main feature of the `MAT` environment is that it is reentrant as shown below:

```
\[ \begin{MAT}{0c.c9}
\first-
1 & 2 \\. 3 &
\begin{MAT}{c:c}
a & b \\\.
c & d \\
\end{MAT} \\
\end{MAT}
\]
```



IMPORTANT: The package can manage maximum reentrance of **8** levels.

2 Some example with balancing

The effect of various balancing is seen below:

```
\[
\begin{MAT}{|c|c|c|}
\first-
1 & 22 & 333 \\
\frac{1}{2} & 1 & 1 \\
\frac{1}{2} & 1 & 1 \\
\end{MAT}
\quad
\begin{MAT}{(r){|c|c|c|}}
\first-
1 & 22 & 333 \\
\frac{1}{2} & 1 & 1 \\
\frac{1}{2} & 1 & 1 \\
\end{MAT}
\quad
\begin{MAT}{(c){|c|c|c|}}
\first-
1 & 22 & 333 \\
\frac{1}{2} & 1 & 1 \\
\frac{1}{2} & 1 & 1 \\
\end{MAT}
\]
```

| | | |
|---------------|----|-----|
| 1 | 22 | 333 |
| $\frac{1}{2}$ | 1 | 1 |
| $\frac{1}{2}$ | 1 | 1 |

| | | |
|---------------|----|-----|
| 1 | 22 | 333 |
| $\frac{1}{2}$ | 1 | 1 |
| $\frac{1}{2}$ | 1 | 1 |
| $\frac{1}{2}$ | 1 | 1 |

| | | |
|---------------|----|-----|
| 1 | 22 | 333 |
| $\frac{1}{2}$ | 1 | 1 |
| $\frac{1}{2}$ | 1 | 1 |
| $\frac{1}{2}$ | 1 | 1 |

and this is another example

```
\[
  \begin{MAT} (b) { |c|c|c| }
    \first-
    1 & 22 & 333 \\
    \frac{1}{2} & 1 & 1 \\
    \frac{1}{2} & 1 & 1
  \end{MAT}
  \quad
  \begin{MAT} (e) { |c|c|c| }
    \first-
    1 & 22 & 333 \\
    \frac{1}{2} & 1 & 1 \\
    \frac{1}{2} & 1 & 1
  \end{MAT}
\]
```

| | | |
|---------------|----|-----|
| 1 | 22 | 333 |
| $\frac{1}{2}$ | 1 | 1 |
| $\frac{1}{2}$ | 1 | 1 |

| | | |
|---------------|----|-----|
| 1 | 22 | 333 |
| $\frac{1}{2}$ | 1 | 1 |
| $\frac{1}{2}$ | 1 | 1 |

3 An example with minimal size setting

It is possible to specify the minimal size of the item inside a **MAT** environment:

```
\[ \left[
  \begin{MAT} (@,50pt,20pt) {c.c}
    1 & 22 \\
    \frac{1}{2} & 1 \\
  \end{MAT}
\right] \]
```

$$\left[\begin{array}{cc} 1 & 22 \\ \hline \frac{1}{2} & 1 \end{array} \right]$$

It is possible to specify the total minimal size of a **MAT** environment, as shown here

```
\[ \left[ \begin{array}{c|c} 1 & 22 \\ \hline \frac{1}{2} & 1 \end{array} \right] \times \left[ \begin{array}{c} x \\ y \end{array} \right] = \left[ \begin{array}{c} 2 \\ \frac{3}{2} \end{array} \right]
```

$$\left[\begin{array}{c|c} 1 & 22 \\ \hline \frac{1}{2} & 1 \end{array} \right] \times \left[\begin{array}{c} x \\ y \end{array} \right] = \left[\begin{array}{c} 2 \\ \frac{3}{2} \end{array} \right]$$

4 An example with various size rules

This example shows the use of various size rule in **MAT** environment:

```
\[ \begin{MAT} (e,10pt,10pt){0c1c2c3c4c5c6c7c8c9}
\first0
* & * & * & * & * & * & * & * & * & * \\1
* & * & * & * & * & * & * & * & * & * \\2
* & * & * & * & * & * & * & * & * & * \\3
* & * & * & * & * & * & * & * & * & * \\4
* & * & * & * & * & * & * & * & * & * \\5
* & * & * & * & * & * & * & * & * & * \\6
* & * & * & * & * & * & * & * & * & * \\7
* & * & * & * & * & * & * & * & * & * \\8
* & * & * & * & * & * & * & * & * & * \\9 \end{MAT} \]
```

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| * | * | * | * | * | * | * | * | * | * |
| * | * | * | * | * | * | * | * | * | * |
| * | * | * | * | * | * | * | * | * | * |
| * | * | * | * | * | * | * | * | * | * |
| * | * | * | * | * | * | * | * | * | * |
| * | * | * | * | * | * | * | * | * | * |
| * | * | * | * | * | * | * | * | * | * |
| * | * | * | * | * | * | * | * | * | * |
| * | * | * | * | * | * | * | * | * | * |
| * | * | * | * | * | * | * | * | * | * |

5 The \addpath command

Is is possible to add paths to the **MAT** environment. The syntax is the following

```
\begin{MAT} ..... {....}
..... \\
..... \\
..... \\
\addpath{('x','y','rule')'path'}
.
.
.
\addpath{('x','y','rule')'path'}
\end{MAT}
```

where

x and **y** are the integer coordinates of the starting corner. The down left corner is at $x = 0, y = 0$.

rule is the code of a valid rule as described in table 3.


path is a string describing the path. Each letter of the string is a movement coded as follows:

Table 4.

| letter | direction |
|----------|----------------------------|
| l | left movement and drawing |
| r | right movement and drawing |
| u | up movement and drawing |
| d | down movement and drawing |

The following example shows the use of \addpath,

```
\[ \begin{MAT}[5pt]{|cccccl}
\first-
* & * & * & * & * \\
* & * & * & * & * \\
* & * & * & * & * \\
* & * & * & * & *
\addpath{(1,1,0)ruld}
\addpath{(4,3,;)lldrrd1l} \\-
\end{MAT} \]
```



IMPORTANT: The commands \addpath must be put **in front of** the last \\ command.

This is another example

```
\[ \left(\begin{array}{cccccc} 1 & * & * & * & * & * \\ 0 & 11 & * & * & * & * \\ 0 & 0 & 111 & * & * & * \\ 0 & 0 & 0 & 1111 & * & * \\ 0 & 0 & 0 & 0 & 11111 & * \\ 0 & 0 & 0 & 0 & 0 & 11111 \\ \end{array}\right) \right] \\ \addpath{(0,5,.)rdrdrdrd} \\ \end{array}\right) \]
```

$$\left(\begin{array}{cccccc} 1 & * & * & * & * & * \\ 0 & 11 & * & * & * & * \\ 0 & 0 & 111 & * & * & * \\ 0 & 0 & 0 & 1111 & * & * \\ 0 & 0 & 0 & 0 & 11111 & * \\ 0 & 0 & 0 & 0 & 0 & 11111 \end{array} \right)$$

6 An example with reentrance

This final example shows a slightly more complex (reentrant) definition in which the **MAT** environment is used:

```

\def\rec(#1){\expandafter\recurse#1-\end}
\def\recurse#1#2\end{%
  \if\noexpand#1-\def\next##1##2{ }%
  \else\let\next=\recurse\fi%
  \expandafter\next{#1}{#2}%
}%
\def\recursea#1#2{%
  \bgroup
    \begin{MAT}[0pt]{l:c:r}
      \aligntop
      \rec(#2) & #1 & \rec(#2) \\
      & #1 & \rec(#2) & #1 \\
      \alignbottom
      \rec(#2) & #1 & \rec(#2) \\
      \end{MAT}
    \egroup
}
\small
\[
  \recurse\clubsuit\diamondsuit\heartsuit\end
\]

```

